

US009908669B2

(12) United States Patent

Stratton

(10) Patent No.: US 9,908,669 B2

(45) **Date of Patent:** Mar. 6, 2018

(54) ANTI-GLUG DEVICE FOR LIQUID CONTAINERS AND POUR SPOUTS

(71) Applicant: Container Packaging Systems, Inc.,

Churubusco, IN (US)

(72) Inventor: Jon Stratton, Churubusco, IN (US)

(73) Assignee: Container Packaging Systems, Inc.,

Churubusco, IN (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 15/614,198

(22) Filed: Jun. 5, 2017

(65) Prior Publication Data

US 2017/0267425 A1 Sep. 21, 2017

Related U.S. Application Data

- (63) Continuation-in-part of application No. 14/879,442, filed on Oct. 9, 2015, now Pat. No. 9,669,972.
- (60) Provisional application No. 62/061,884, filed on Oct. 9, 2014.

| (51) | Int. Cl. | |
|------|------------|-----------|
| , , | B65D 47/32 | (2006.01) |
| | B65D 25/42 | (2006.01) |
| | B65D 47/06 | (2006.01) |
| | B65D 47/04 | (2006.01) |
| | B65D 25/46 | (2006.01) |
| | B65D 25/44 | (2006.01) |
| | B65D 25/32 | (2006.01) |
| | B67D 3/00 | (2006.01) |

(52) U.S. Cl.

 B65D 47/043 (2013.01); **B65D 47/063** (2013.01); **B65D 47/06** (2013.01); **B67D 3/00** (2013.01)

(58) Field of Classification Search

CPC B65D 25/32; B65D 25/42; B65D 25/44; B65D 25/465; B65D 47/32; B65D 47/043; B65D 47/063 USPC 222/108–111, 478, 541.9, 526–537, 222/566–574, 543

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

| 5,791,529 A * | 8/1998 | Mukai B65D 23/00 |
|---------------|--------|-----------------------|
| | | 222/478 |
| 6,845,885 B2* | 1/2005 | Morgenroth B65D 47/06 |
| | | 222/109 |
| 8,011,535 B2* | 9/2011 | Tauber B65D 47/122 |
| | | 215/330 |
| 9,669,972 B2* | 6/2017 | Stratton B65D 47/32 |

^{*} cited by examiner

Primary Examiner — Paul R Durand
Assistant Examiner — Andrew P Bainbridge
(74) Attorney, Agent, or Firm — Lempia Summerfield
Katz LLC

(57) ABSTRACT

A lid for a liquid container has a lid wall with a perimeter, a top side surface, and an underside surface. The lid has an anti-glug device carried on the lid wall and positioned to coincide with a dispensing orifice in the lid wall. The anti-glug device has a channel that partly circumferentially surrounds the dispensing orifice. Terminal ends of the channel define a circumferential gap therebetween. One or more air vents are formed axially through a part of the channel and are disposed circumferentially opposite the circumferential gap.

25 Claims, 12 Drawing Sheets

